

Indian Valley Industries, Inc.

Technical Data Sheet

IVI High Density Coir Logs/Bio Fiber Rolls Log Length - 10 LF (3.05 m) or 20 LF (6.10 m)

IVI Coir (Coconut) Sediment Control logs are a reliable solution for stream and lakeshore erosion problems as well as slope stabilization. Manufactured with 100% coir fibres encased in a rhombic coir netting, ivi coir logs outperform all other sediment logs in the most demanding situations and for the longest duration.

Supplied in dimensions listed below, IVI High Density Coir Logs provide the user an opportunity to select the coir log, which meets their application requirements in the most cost effective manner. Easily installed using no special equipment, High Density Coir Logs help create a growth environment for plant materials in which vegetation can be restored and fragile ecosystems are protected.

PRODUCT TEST DATA			
	12-inch Diameter Roll (305mm)	16-inch Diameter Roll (406mm)	20-inch Diameter Roll (508mm)
Unit Weight	7.0 lbs/ft (10.4 kg/m)	12.5 lbs/ft (18.6 kg/m)	19.5 lbs/ft (28.8kg/m)
Core Density	9.0 lbs/cu.ft (145 kg/cu.m)	9.0 lbs/cu.ft (145 kg/cu.m)	9.0 lbs/cu.ft (145 kg/cu.m)
Outer Netting	3-ply coir with 0.40 in. dia (1cm dia.)		
Outer Netting Break- ing Strength	90 lbs (400N)		
Outer Netting Mesh Size	2" x 2" Rhombic mesh with handknotted junctions		
Inner Core	Unsorted, double-cleaned, well-graded, coir fiber		

The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. Except when agreed to in writing for specific conditions of use, no warranty or guarantee expressed or implied is made regarding the performance of any product, since the manner of use and handling are beyond our control. Nothing contained herein is to be construed as permission or as a recommendation to infringe any patent.