

# Indian Valley Industries, Inc.

## Technical Data Sheet

### IVI 3611W Wire Back Silt Fence

<b>Roll Size:</b>	3' x 100'
<b>Stakes:</b>	1.5" x 1.5" x 48" Pointed Hardwood Stakes
<b>Stake Spacing:</b>	10' on center
<b>Wire:</b>	14 gauge, 6" x 6" galvanized welded wire
<b>Attachment:</b>	Hog rings at top and mid-section on 24" spacing

A woven polypropylene fabric will meet or exceed the following typical values when tested in accordance with the proper ASTM test methods. Complies to AASHTO specification M-288 and ASTM D6461.

<b>PRODUCT TEST DATA</b>		
<b>Physical Property</b>	<b>Test Method</b>	<b>MARV</b>
<b>Composition</b>		Polypropylene
<b>Color</b>		Black
<b>Tensile Strength - Grab</b>	ASTM D-4632	124 lbs x 124 lbs
<b>Elongation</b>	ASTM D-4632	15%
<b>Puncture</b>	ASTM D-4833	65 lbs
<b>Mullen Burst</b>	ASTM D-3786	205 psi
<b>Trapezoidal Tear</b>	ASTM D-4533	65 lbs.
<b>U.V Resistance % Retained (500 hrs)</b>	ASTM D-4355	70%
<b>Apparent Opening Size (AOS)</b>	ASTM D-4751	30 US Std. Sieve
<b>Permittivity</b>	ASTM D-4491	0.05 Sec-1
<b>Water Flow Rate</b>	ASTM D-4491	15 gal/min/ft <sup>2</sup>

The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. Except when agreed to in writing for specific conditions of use, no warranty or guarantee expressed or implied is made regarding the performance of any product, since the manner of use and handling are beyond our control. Nothing contained herein is to be construed as permission or as a recommendation to infringe any patent.